

# Aerators



The application of the right aerator at a tap is important in combination with electric water heaters. The new special aerator CSP mixes the water flow with air and therefore provides a constant, soft and enlarged flow without splashing. The aerated water flow supports the energy - and water saving use of mini instantaneous water heaters. The aerators are manufactured with precise plastics technology and are available as inserts only or as a set with threaded housing suitable for the installed tap.



### CSP 3

Aerator insert < 3.5 l/min., for M22/24 threaded housing at the tap, perfect for an instant water heater < 5 kW, Art.-No. 00421



### CSP 3a

Aerator for taps < 3.5 l/min, with M24 male threaded housing for taps perfect for an instant water heater < 5 kW, Art.-No. 0043



### CSP 3i

Aerator for taps < 3.5 l/min, with M22 female threaded housing for taps perfect for an instant water heater < 5 kW, Art.-No. 0042



### CSP 6

Aerator insert for M22/24 threaded housing at the tap, perfect for an instant water heater 5 – 13 kW, Art.-No. 00461



### CSP 6a

Aerator for taps, with M24 male threaded housing for taps perfect for an instant water heater 5 – 13 kW, Art.-No. 0047



### CSP 6i

Aerator for taps, with M22 female threaded housing for taps perfect for an instant water heater 5 – 13 kW, Art.-No. 0046



### CSM

Spray insert < 3.5 l/min, for M22/24 threaded housing at the tap perfect for an instant water heater < 5 kW, Art.-No. 00502



### CSMa

In formed packaging: special aerator with M24 male threaded housing for taps provides a non-aerated spray < 3,5 l/min, Art.-No. 00491



### CSS

Special aerator insert for M22/24 threaded housing at the vented tap, required for open-outlet storage heaters, Art.-No. 00504



### CSSi

Special flow regulator with M22 female thread for vented taps with male thread at the outlet, required for open-outlet storage heaters, Art.-No. 89125

Aerator type	Instantaneous water heater			Storage heater
	M..3 / M..4	M..6 / M..7	C.. 6–13	S 5
CSP 3		*	—	—
CSP 6	—			—
CSM		—	—	—
CSS	—	—	—	

\* For MCX 6/7 SMARTRONIC® only.