

# SLOWOOD

SCHEMA TECNICA PRODOTTO - TECHNICAL DATA SHEET

Gres fine porcellanato colorato in massa- Fully-coloured porcelain tiles

## DATI GENERALI - GENERAL DATA

SERIE-SERIES :	<b>SLOWOOD</b>
FORMATI-SIZES :	<b>30x120 - 20x120 - 15x120</b>
NOMI-NAMES :	<b>AVOCADO - SAMBUCO - NOCCILOLO - GELSO - MANDORLO</b>
COLORI-COLOURS :	<b>BEIGE - SABBIA - NOCCIOLA - GRIGIO - MARRONE</b> <b>BEIGE - SAND - LIGHT BROWN - GREY - BROWN</b>
SUPERFICIE-SURFACE :	<b>MAT</b>
NR. COLORI-NR. COLOURS :	<b>5</b>










## ACCESSORI - ACCESSORIES

FONDI-TILES :	<b>X</b>	BATTISCOPIA-BULLNOSE:	<b>X</b>
DECORI-DECORS :		GRADINO-STEP:	<b>X</b>

USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Interno  
Indoor Floor Tile - Outdoor Floor Tile - Indoor Wall Tile

## CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)  
Appendice G - Classe di appartenenza B1a / Annex G - Group B1a

RESISTENZA AL GELO FROST RESISTANCE		<b>SI</b>	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) HARDNESS (MOHS)		<b>7</b>	UNI EN 101
RESISTENZA ALL'ABRASIONE PROFONDA RESISTANCE TO DEEP ABRASION		<b>≤ 175 mm<sup>3</sup></b>	EN ISO 10545-6
SPESSORE IN BASE AL FORMATO THICKNESS IN REFERENCE TO THE SIZES		<b>10,5 mm</b>	EN ISO 10545-2
SCIVOLOSITA' SLIPPERINESS		<b>R 10</b>	DIN 51130
		<b>A</b>	DIN 51097
RESISTENZA ALLE MACCHIE RESISTANCE TO STAINING		<b>5</b>	EN ISO 10545-14
RESISTENZA CHIMICA RESISTANCE TO CHEMICALS		<b>A-LA-HA</b>	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE/MODULO DI ROTTURA BENDING STRENGTH/BREAKING STRENGTH		<b>≥ 35 N/mm<sup>2</sup></b>	EN ISO 10545-4
ASSORBIMENTO WATER ABSORPTION		<b>≤ 0,5%</b>	EN ISO 10545-3