

AZULEJOS

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET
Gres porcellanato - Porcelain tiles

DATI GENERALI - GENERAL DATA

SERIE-SERIES :	AZULEJOS
FORMATI-SIZES :	20x20
NOMI-NAMES :	PORTUGAL-ESTORIL-LISBOA-ALFAMA MIX-OPORTO-RIBEIRA MIX-BAIXA ROSSIO MIX
COLORI-COLOURS :	BEIGE-GRIGIO SCURO-DEC.UNICO BEIGE-DEC.MIX BEIGE-DEC.UNICO AZZURRO DEC.MIX AZZURRO-DEC.UNICO NERO-DEC.MIX NERO <i>beige-dark grey-only beige dec.-mix beige dec.-only light blu dec.-mix light blu dec. only black dec.-mix black dec.</i>
SUPERFICIE-SURFACE :	MAT
NR. COLORI-NR. COLOURS :	8










ACCESSORI - ACCESSORIES

FONDI-TILES :	X	BATTISCOPIA-BULLNOSE:	
DECORI-DECORS:		GRADINO-STEP:	

USO PREVALENTE - USAGE: Pav. Interno - Pav Esterno - Riv. Esterno
Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile

CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)
Appendice G - Classe di appartenenza **B I a** - Class of **B I a**

RESISTENZA AL GELO <i>FROST RESISTANCE</i>		SI	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) <i>HARDNESS (MOHS)</i>		6	UNI EN 101
RESISTENZA ALL'ABRASIONE DELLA SUPERFICIE- PEI <i>RESISTANCE TO SURFACE ABRASION-PEI</i>		PEI IV	EN ISO 10545-7
SPESSORE IN BASE AL FORMATO <i>THICKNESS IN REFERENCE TO THE SIZES</i>		10 mm	EN ISO 10545-2
SCIVOLOSITA' <i>SLIPPERINESS</i>		>μ 0,40 Attrito soddisfacente <i>Acceptable Friction</i>	D.M. 236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE <i>RESISTANCE TO STAINING</i>		5	EN ISO 10545-14
RESISTENZA CHIMICA <i>RESISTANCE TO CHEMICALS</i>		A-LA-HA	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE/MODULO DI ROTTURA <i>BENDING STRENGTH/BREAKING STRENGTH</i>		≥ 35 N/mm²	EN ISO 10545-4
ASSORBIMENTO <i>WATER ABSORPTION</i>		≤ 0,5%	EN ISO 10545-3